



BONO



Туре	floor luminaire
item nr.	17/2501.22
GTIN (EAN)	4022671120067

description

Indirect light is distributed evenly through the opal glass sphere, while a reflector provides homogeneous direct reading light. The indirect light and reading light can be switched and dimmed individually or together using the integrated sensor switch.

luminaire head rotatable and tiltable

BONO, floor luminaire, mat black, LED replaceable by specialist, direct/indirect, IP20

material and dimensions		
color	mat black	
material	aluminium + opal glass	
material	satinised	
dimensions	L 333 mm x B 250 mm x H	
differisions	1,410 mm	
weight	3.4 kg	
light and electric specifications		
lightsource	LED replaceable by specialist	
control	integrated dimmer	
system demand	8 W	
net	890 lm (luminaire/net)	

system demand	8 W
net	890 lm (luminaire/net)
gross	1,120 lm (LED-module/gross)
light color	2,700 K
CRI	90-100
light emission	direct/indirect
degree of protection	IP20
protection class	1
Product type according to EU	
2019/2015 and EU	containing product
2019/2020	
Energy efficiency class of the built-in light source(s)	E
bant in light coardo(b)	

www.helestra.de data sheet 17/2501.22 last updated 05.02.2025 errors and changes excepted