



BONO



Туре	pendant luminaire
item nr.	56/2501.70
GTIN (EAN)	4022671120661

description

material and dimensions

Each pendant luminaire is individually height-adjustable with EASY-Lift

Indirect light is evenly distributed by the opal glass sphere, while a reflector provides homogeneous direct light downwards

BONO, pendant luminaire, coffee, LED replaceable by specialist, direct/indirect, IP20

suspension length weight 7.3 kg light and electric specifications lightsource control Casambi Casambi System demand et		
dimensions L 1,415 mm x B 100 mm x H 2,100 mm height adjustment suspension length weight 7.3 kg light and electric specifications lightsource control Casambi Casambi system demand net 4,450 lm (luminaire/net) gross 5,600 lm (LED-module/gross) light color CRI 90-100 light emission direct/indirect degree of protection protection class 1 Product type according to EU 2019/2015 and EU 2019/2020 Energy efficiency class of the built-in light source(s) LED replaceable by specialist dimmable trailing/leading edge optionally available with CASAMBI control system demand 42 W Ret 4,450 lm (luminaire/net) gross 5,600 lm (LED-module/gross) light color 2,700 K CRI 90-100 light emission direct/indirect degree of protection IP20 protection class 1 Product type according to EU 2019/2015 and EU 2019/2020 Energy efficiency class of the built-in light source(s) E CASAMBI CBU-TED Bluetooth Dimmer item nr. 6100	color	coffee
height adjustment EASY-LIFT height adjustment suspension length 10 mm - 1,900 mm weight 7.3 kg light and electric specifications lightsource LED replaceable by specialist dimmable trailing/leading edge Casambi Optionally available with CASAMBI control system demand 42 W net 4,450 lm (luminaire/net) gross 5,600 lm (LED-module/gross) light color 2,700 K CRI 90-100 light emission direct/indirect degree of protection IP20 protection class 1 Product type according to EU 2019/2015 and EU containing product 2019/2020 Energy efficiency class of the built-in light source(s) E CASAMBI CBU-TED Bluetooth Dimmer item nr. 6100	material	aluminium + Opalglas weiss
suspension length weight 7.3 kg light and electric specifications lightsource control Casambi Casambi System demand et	dimensions	,
light and electric specifications lightsource Control Casambi Casambi Casambi Casambi Casambi System demand net 4,450 lm (luminaire/net) gross 5,600 lm (LED-module/gross) light color CRI 90-100 light emission direct/indirect degree of protection protection class 1 Product type according to EU 2019/2015 and EU 2019/2020 Energy efficiency class of the built-in light source(s) accessory name CASAMBI CBU-TED Bluetooth Dimmer item nr. 6100	height adjustment	EASY-LIFT height adjustment
light and electric specifications lightsource Control Casambi Casambi Casambi System demand net 42 W net 4,450 Im (luminaire/net) gross 5,600 Im (LED-module/gross) light color 2,700 K CRI 90-100 light emission direct/indirect degree of protection protection class 1 Product type according to EU 2019/2015 and EU 2019/2020 Energy efficiency class of the built-in light source(s) accessory name CASAMBI CBU-TED Bluetooth Dimmer item nr. 6100	suspension length	10 mm - 1,900 mm
lightsource Control Casambi Casambi Casambi Casambi System demand net 42 W net 4,450 lm (luminaire/net) gross 5,600 lm (LED-module/gross) light color CRI 90-100 light emission direct/indirect degree of protection protection class 1 Product type according to EU 2019/2015 and EU 2019/2020 Energy efficiency class of the built-in light source(s) accessory name CASAMBI CBU-TED Bluetooth Dimmer item nr. 6100	weight	7.3 kg
control dimmable trailing/leading edge Casambi optionally available with CASAMBI control system demand 42 W net 4,450 lm (luminaire/net) gross 5,600 lm (LED-module/gross) light color 2,700 K CRI 90-100 direct/indirect degree of protection IP20 protection class 1 Product type according to EU 2019/2015 and EU containing product 2019/2020 Energy efficiency class of the built-in light source(s) CASAMBI CBU-TED Bluetooth Dimmer item nr. 6100	light and electric specifications	
control edge Casambi Optionally available with CASAMBI control system demand 42 W net 4,450 lm (luminaire/net) gross 5,600 lm (LED-module/gross) light color 2,700 K CRI 90-100 light emission direct/indirect degree of protection IP20 protection class 1 Product type according to EU 2019/2015 and EU containing product 2019/2020 Energy efficiency class of the built-in light source(s) CASAMBI CBU-TED Bluetooth Dimmer item nr. 6100	lightsource	LED replaceable by specialist
CASAMBI control system demand 42 W net 4,450 lm (luminaire/net) gross 5,600 lm (LED-module/gross) light color 2,700 K CRI 90-100 light emission direct/indirect degree of protection IP20 protection class 1 Product type according to EU 2019/2015 and EU containing product 2019/2020 Energy efficiency class of the built-in light source(s) E CASAMBI CBU-TED Bluetooth Dimmer item nr. 6100	control	• •
net 4,450 lm (luminaire/net) gross 5,600 lm (LED-module/gross) light color 2,700 K CRI 90-100 light emission direct/indirect degree of protection IP20 protection class 1 Product type according to EU 2019/2015 and EU containing product 2019/2020 Energy efficiency class of the built-in light source(s) CASAMBI CBU-TED Bluetooth Dimmer item nr. 6100	Casambi	
gross 5,600 lm (LED-module/gross) light color 2,700 K CRI 90-100 light emission direct/indirect degree of protection IP20 protection class 1 Product type according to EU 2019/2015 and EU containing product 2019/2020 Energy efficiency class of the built-in light source(s) E CASAMBI CBU-TED Bluetooth Dimmer item nr. 6100	system demand	42 W
light color 2,700 K CRI 90-100 light emission direct/indirect degree of protection IP20 protection class 1 Product type according to EU 2019/2015 and EU containing product 2019/2020 Energy efficiency class of the built-in light source(s) CASAMBI CBU-TED Bluetooth Dimmer item nr. 6100	net	4,450 lm (luminaire/net)
CRI 90-100 light emission direct/indirect degree of protection IP20 protection class 1 Product type according to EU 2019/2015 and EU containing product 2019/2020 Energy efficiency class of the built-in light source(s) E CASAMBI CBU-TED Bluetooth Dimmer item nr. 6100	gross	5,600 lm (LED-module/gross)
light emission direct/indirect degree of protection IP20 protection class 1 Product type according to EU 2019/2015 and EU containing product 2019/2020 Energy efficiency class of the built-in light source(s) accessory name CASAMBI CBU-TED Bluetooth Dimmer item nr. 6100	light color	2,700 K
degree of protection IP20 protection class 1 Product type according to EU 2019/2015 and EU containing product 2019/2020 Energy efficiency class of the built-in light source(s) E CASAMBI CBU-TED Bluetooth Dimmer item nr. 6100	CRI	90-100
protection class 1 Product type according to EU 2019/2015 and EU containing product 2019/2020 Energy efficiency class of the built-in light source(s) accessory name CASAMBI CBU-TED Bluetooth Dimmer item nr. 6100	light emission	direct/indirect
Product type according to EU 2019/2015 and EU 2019/2020 Energy efficiency class of the built-in light source(s) accessory name CASAMBI CBU-TED Bluetooth Dimmer item nr. 6100	degree of protection	IP20
2019/2015 and EU containing product 2019/2020 Energy efficiency class of the built-in light source(s) E CASAMBI CBU-TED Bluetooth Dimmer item nr. 6100	protection class	1
built-in light source(s) accessory name CASAMBI CBU-TED Bluetooth Dimmer item nr. 6100		containing product
name CASAMBI CBU-TED Bluetooth Dimmer item nr. 6100	Energy efficiency class of the built-in light source(s)	Е
name Bluetooth Dimmer item nr. 6100	accessory	
	name	
short text CASAMBI, accessory	item nr.	6100
	short text	CASAMBI, accessory

www.helestra.de data sheet 56/2501.70 last updated 22.04.2025 errors and changes excepted